

NOVEDADES ENRICH

PROFILE CIRCULAR LED PENDANT LIGHT

Circle Ring LED Pendant Light

- Profile size: W40*H60mm
- Diameter: 0.45m, 0.6m, 0.8m, 0.9m, 1.0m, 1.2m, 1.5m, 1.8m, 2.0m, 2.4m, 3.0m, 4.0m, 5.0m
- Material: Aluminum
- Voltage: AC220-240V/100-277V
- CCT: 3000K/4000K/6000K
- Dimming: 0-10V/DALI
- Warranty: 5 Years

Technical diagrams showing different sizes and internal components of the Circle Ring LED Pendant Light.

★ Feature

- High efficiency LED board
- Range of size options,OEM available
- Wide-beam light distribution
- CRI>80
- PF>0.95.no flicker
- UGR<19

★ Benefit

- Custom fit options available
- Contemporary style
- Luminaire design
- Energy efficient solution
- European / America control gear

★ Control Option

- Fixed or Non Dimmable
- 0-10V Dimmable
- DALI Dimmable

CINTA LED NEON FLEX 360°
30mm Diameter 360degree Flexible Soft LED Chandelier

Product Parameters

Input Voltage : DC12V / DC24V
 Diameter: Ø22mm
 Beam Angle: 360°
 Length: 5meter/roll
 Material: Copper + Silicone
 LED Chip : SANAN SMD2835
 Emitting Color : 3000K / 4000K / 6000K / Red / Green / Blue / Yellow / Pink / Purple
 Cuttable: Yes
 Luminous Flux : 100Lm/W
 CRI :>80Ra
 PF :>0.95
 Function Option : ON/OFF Dimmable
 IP Grade : IP67
 Warranty : 5years

360°
Super Bright,Low dark area

Waterproof IP67 grade

Soft,area bendable

S Shape Curve Profile LED Linear Light

★ Data sheet

*Input voltage : AC220-240V/AC100-277V,50/60HZ
 *Material : 6063 extruded aluminum profile + PPD/LA diffuser
 *LED chip : SANAN SMD2835
 *Driver : LfUd (Non dimming),BOKE (Dimming)
 *Dimming option :Non dimming / 0-10V dimming / DALI dimming
 *Color Temperature : 3000K / 4000K / 6000K
 *Beam angle : 120°
 *Power factor : >0.95
 *CRI : >82Ra
 *UGR : <19
 *Flicker free: Yes
 *Aluminum finish : Black / White / Silver / Golden
 *Installation method : Suspension / Ceiling surface / Recessed
 *Installation accessories : include
 *Warranty : 5years

★ Product size

★ Aluminium section size

Model	Power	Luminous flux	Size	Part quantity	CRI	CCT	Voltage
LS6060-S1	10W	1000Lm	L890*W235mm	1 part	82	3000K 4000K 6000K	AC220-240V AC100-277V
LS6060-S2	15W	1500Lm	L1230*W306mm	2 parts	82		
LS6060-S3	20W	2000Lm	L1455*W355mm	2 parts	82		
LS6060-S4	30W	3000Lm	L1855*W395mm	2 parts	82		
LS6060-S5	40W	4000Lm	L2160*W500mm	2 parts	82		
LS6060-S6	50W	5000Lm	L2590*W590mm	2 parts	82		
LS6060-S7	60W	6000Lm	L2870*W645mm	2 parts	82		
LS6060-S8	75W	7500Lm	L3435*W765mm	2 parts	82		
LS6060-S9	120W	12000Lm	L5250*W1560mm	4 parts	82		
LS6060-S10	140W	14000Lm	L5700*W1730mm	4 parts	82		
LS6060-S11	160W	16000Lm	L7115*W1525mm	4 parts	82		
LS6060-S12	180W	18000Lm	L8325*W1815mm	6 parts	82		
LS6060-S13	240W	24000Lm	L9940*W2110mm	6 parts	82		

ENRICH

VALOR NETO

ENRICH

VALOR NETO

ALUMINIUM PROFILE LED LINEAR LIGHT

Product Parameters

Input Voltage : AC100-277V / AC220-240V,50-60HZ
 Material : 6063 Aluminium Profile + Opal Diffuser / Microprism Diffuser
 LED Chip : SANAN SMD2835
 Driver Brand : BOKE (220-240V) / Cupower (100-277V)
 Color Temperature : 3000K / 4000K / 6000K
 Luminous Flux : 100-110Lm/W
 CRI :>80Ra
 PF :>0.95
 Flicker Free :Yes
 Function Option :ON/OFF no dimming / 0-10V / Triac / DALI / DALI DT8
 Finish Color Option : Black / White / Silver
 Profile Size Option : W22*H85mm W35*H67mm W35*H70mm W50*H75mm W55*H75mm W75*H75mm W64*H40mm W100*H64mm
 W140*H50mm
 IP Grade : IP20
 Warranty : 5years

Model: EN-3570LS-F6

Driver

70mm

35mm

Width : 35mm / Height : 70mm

Model	Watt	Lumens	Product Size
EN-3570LS20W06-F6	20W	2000lm	L850 W35 H70 mm
EN-3570LS40W12-F6	40W	4000lm	L1280 W35 H70 mm
EN-3570LS80W18-F6	60W	6000lm	L1920 W35 H70 mm
EN-3570LS80W24-F6	80W	8000lm	L2560 W35 H70 mm

ALUMINIUM PROFILE LED LINEAR LIGHT

Product Parameters

Input Voltage : AC100-277V / AC220-240V,50-60HZ
 Material : 6063 Aluminium Profile + Opal Diffuser / Microprism Diffuser
 LED Chip : SANAN SMD2835
 Driver Brand : BOKE (220-240V) / Cupower (100-277V)
 Color Temperature : 3000K / 4000K / 6000K
 Luminous Flux : 100-110Lm/W
 CRI :>80Ra
 PF :>0.95
 Flicker Free :Yes
 Function Option :ON/OFF no dimming / 0-10V / Triac / DALI / DALI DT8
 Finish Color Option : Black / White / Silver
 Profile Size Option : W22*H85mm W35*H67mm W35*H70mm W50*H75mm W55*H75mm W75*H75mm W64*H40mm W100*H64mm
 W140*H50mm
 IP Grade : IP20
 Warranty : 5years

Model: EN-5075LS-F6

Driver

75mm

50mm

Width : 50mm / Height : 75mm

Model	Watt	Lumens	Product Size
EN-5075LS20W06-F6	20W	2000lm	L850 W50 H75 mm
EN-5075LS40W12-F6	40W	4000lm	L1280 W50 H75 mm
EN-5075LS60W18-F6	60W	6000lm	L1920 W50 H75 mm
EN-5075LS80W24-F6	80W	8000lm	L2560 W50 H75 mm